

2014-2015 Notice of Intent Acton Arboretum


A) Taylor Road Parking Lot Renovation and Expansion

B) Bog Boardwalk Renovation and Sidewalk Access from Minot Ave.





Project Site



View at New Entrance (11/2014)





Parking Lot Project Details

- Expand parking capacity
- Add handicap parking spaces
- Create new one-way drive into the lot
- Handle drainage via Rain Garden
- Provide lined paved spaces
- Add new kiosk
- Locate accessible picnic table near kiosk



Improved Universal Accessiblity of "Trailhead"

- accessible pathway to new kiosk
- accessible walkway to handicap picnic table
- accessible portable toilet







Existing Parking Lot Conditions









Rain Gardens filter storm water run-off




Pervious Pavement for Acton Arboretum Parking Lot

Why could we build a pervious parking area at NARA? There is 10'+ of outwash gravel below the parking lot's gravel surface, perfect for storm water recharge.

- 1. The existing Arboretum parking area is situated 2' above ledge, causing groundwater to sit at or near the surface for much of the spring. Would have to build parking lot up 3' to get enough drainage underneath.
- 2. The thin soils below the parking lot are unsorted glacial till, very poor for sub-surface drainage; the parking lot would be saturated for the entire spring, greatly reducing durability of pervious pavement.
- 3. The Arboretum is heavily used, is plowed and sanded regularly during winter months. This causes pervious pore spaces to become clogged.
- 4. According to Nashoba Paving Co. permeable pavement is 3X the cost of impervious pavement.
- 5. Prep requires digging 2' deep and adding a gravel base layer; not possible at Arboretum due to ledge.
- 6. According to D. Waite, Acton Hwy. Dept. the pervious pavement needs yearly maintenance to prevent ruts and potholes from developing.
- 7. Heavy trucks damage pervious pavement. Arboretum has regular trucks and heavy equipment performing work and deliveries.
- 8. Dirt or sand onto paving surface, transported by runoff or vehicles, will contribute to premature clogging and failure.
- 9. We have the ideal location to treat all surface runoff from our impervious surfaces through a rain garden. Benefits of rain gardens are:
 - a) They filter and infiltrate rain water.
 - B) Public education demonstration site for storm water treatment technology.

Other sources: Massachusetts Nonpoint Source Pollution Management; NCDENR Stormwater BMP Manual








Parking Lot Planting Plan For Beautification






Parking Lot Plan 11-19-2014





Rain Garden Planting Plan





Rain Garden Planting Plan

1. Con 2. Yell 3. Upr 4. Indi 5. Cot	SCIENTIFIC NAME Cercis canadensis Morus rubra Fothergilla gardenii Sambucus canadensis Liquidambor styraciflua Salix (sps) Viburnum (sps) Aster (sps) Chelone Littris Eupatorium perfoliatum Monarda Eupatorium purpureum d Covers: servation mix — Bigelow Nur ow Sweet Clover (Melitotus ight Sedge (Carex stricta) and Grass (Sorghastrum nu tail (Typha latifolia)	CONSERVATION RIMB RUB EED	EXISTING WOOD- RET WALL OUT ORASS OUT ORASS OUT ORASS OUT ORASS OUT ORASS OUT ORASS OUT ORASS		TOWN OF ACTON ENGINEERING DEPARTMENT
	TREELI	NE.	J	SURVEY: PVC/QRP DESIGN: PVC	
	J				ACTON ARBORETUM PARKING EXPANSION
			<i>Ş</i> ⁷	DRAFTING: QRP	PARKING EXPANSION
			REVISED: 11/7/2014 11/26/2014	CHECKED: PVC	PLANTING PLAN
			1	SCALE: 1" = 20'	DRAWING NO: 1 DATE: 1/9/2015

og name: Pt\Drawings\Arborebum\Parking Expansion\Tree Planting Plan.



Arboretum Rain Garden Plant List 1-7-2015

M- MONARDA

EB- ELDERBERRY

BS-BONESET

CONSERVATION SEED MIX

WT- WHITE TURTLEHEAD – CLEONE

NEA- NEW ENGLAND ASTER

JP- JOE PYE WEED

SG-SWEETGUM

W- WILLOW (sps)

RMB- RED MULBERRY

RB- REDBUD

VB- VIBURNUM (sps)

FG- FOTHERGILLA -dwarf

UPRIGHT SEDGE

YELLOW SWEET CLOVER

WHITE CLOVER

DAYLILY

MARSHMALLOW

MEADOW RUE

WHITE DAFFODIL


LIRIOPE





Arboretum Bog Boardwalk Rebuild and Sidewalk Access


Notice Of Intent (Conservation Commission 1-7-2015)



Project Site



Proposed Bog Boardwalk Design and Location





Arboretum Bog Boardwalk Rehabilitation

Build new elevated boardwalk through the bog:

- ADA handicap accessible boardwalk
- 4 feet wide with bumper rails; handrails at open water portion
- Non-slip, environmentally-friendly fiberglass surface
- Teak bench
- Educational information panels
- Attach a new ADA paved sidewalk ramp from Minot Ave.





Prototype Boardwalks



(Fibergrate product website)







Building Supplies

- Traditional, pressure
 treated lumber materials
- Materials will be handcarried in to site
- •Galvanized pipes into substrate with pipe points attached to the bottom.



- Quality fiberglass reinforced plastic (FRP) decking material
- •Light-weight, low maintenance, corrosion resistant, impact resistant, high strength.
- •Significant ergonomic and safety benefits.
- More light pass through to plants below



2" Pipe Point (PLD011)

The Pipe Point can be used in any situation, but is very helpful where the Lake bottom is extra firm



ISO 9001:2008 Certified

Patriot Foundry & Castings, LLC RDS Dock Hardware 324 Hill Road P.O. Box 298 West Franklin, NH 03235






Concept Drawing: Paved sidewalk to boardwalk from Minot Ave.





Engineered Plans for Paved Sidewalk from Minot Ave.






Wetlands Protection Act and Sidewalks

- Acton By-Law Section F4.6 says that strict compliance may be waived when such action is in the public interest. Sidewalk access is in the public interest.
- Examples of Acton sidewalks built with 0' setback from wetlands:
 - Stow St. by RR Sta.
 - Main St. near 2A
 - Minot Av. near Conant School
 - 2A Great Road near Nagog Mall
 - 2A Great Road Davis Rd.






Sidewalk on Central St. Between Mt. Hope Cemetery and Summer Street







Cross Sections A&B



Minot Av. Sidewalk Ramp Cross Section A



Minot Av. Sidewalk Ramp Cross Section B



Comparison drawing: Sidewalk 1 – on the right and 2- on the left

Sidewalk 2:


•10,000 cubic ft. fill under pavement

7 trees removed

•450 sq. ft. wetlands

•270' distance from crosswalk

•170' long sidewalk



Sidewalk 1:

•7,145 cubic ft. fill under pavement

•5 trees removed

•0 sq. ft. wetlands fill

•0' distance from crosswalk

•128' long sidewalk